## **EUROPEAN PATENT OFFICE**

## Patent Abstracts f Japan

**PUBLICATION NUMBER** 

60123084

**PUBLICATION DATE** 

01-07-85

**APPLICATION DATE** 

08-12-83

APPLICATION NUMBER

58231742

APPLICANT: MATSUSHITA ELECTRIC IND CO LTD;

INVENTOR: KOGA KEISUKE:


INT.CL.

H01S 3/18 // G02B 6/26

TITLE

**SEMICONDUCTOR LIGHT** 

**GENERATOR** 



ABSTRACT :

PURPOSE: To miniaturize and stabilize the titled generator, and to improve coupling efficiency between a light source and an optical transmission line by using a surface light-emitting semiconductor laser as a semiconductor laser and employing a device consisting of a periodic waveguide, in which a plurality of optical waveguide layers are laminated on an active layer in the surface light-emitting semiconductor laser, as a resonator.

CONSTITUTION: A surface light-emitting semiconductor laser has laser oscillation action while using a substrate surface 9 and a laminated type optical waveguide layer 12, which is grown on an active layer 11 in an epitaxial manner and has a diffraction grating function, as both resonator surfaces. Oscillation wavelength can be selected arbitrarily by changing the thickness and refractive index of the laminated type optical waveguide layer 12 having a periodic waveguide within a range of the gains of the active layer 11. Since output signals can be extracted in large areas and under collimating states in the surface light-emitting semiconductor laser, spot size can be reduced when output signal beams are distributed by using a transmission type diffraction grating 14. A resist diffraction grating is prepared on the surface containing a light-emitting region in the surface light-emitting semiconductor laser, and etched, thus transferring the diffraction grating pattern on the light-emitting surface of the surface light- emitting semiconductor laser 8.

COPYRIGHT: (C) JPO